

- Bij uitstek geschikt - Très approprié - Muy adecuado - Ideal geeignet
 □ Beperkt geschikt - Approprié - Adecuado - Eingeschränkt geeignet

ISO ■	ISO □	NL	FR	ES	DE
P 11 S800 N/mm ²	P 11 S800 N/mm ²	Ongelegeerd en gelegeerd staal ≤600 N/mm² 1.0037 (St37), 1.0038 (S235JR G2), 1.00402 (C22), 1.1178 (C30E)	Aciers non-alliés ou faiblement alliés ≤600 N/mm² 1.0037 (A37), 1.0038 (E 24-2 Ne), 1.00402 (1C20), 1.1178 (1C30)	Acero no aleado ≤600 N/mm² 1.0037 (S235JR), 1.0038 (S235JR G2), 1.0402 (F.112), 1.1178 (C30E)	Unlegierter und legierter Stahl ≤600 N/mm² 1.0037 (St37), 1.0038 (S235JR G2), 1.00402 (C22), 1.1178 (C30E)
P 12 S850 N/mm ²	P 12 S850 N/mm ²	Ongelegeerd en gelegeerd staal 600 - 850 N/mm² 1.0050 (St50-2), 1.0070 (St70-2), 1.0301 (C10), 1.0503 (C45), 1.1121 (Ck10), 1.1191 (C45E), 1.0718 (11SMnPb30), 1.0736 (11SMn37)	Aciers non-alliés ou faiblement alliés 600 - 850 N/mm² 1.0050 (A50-2), 1.0070 (A70-2), 1.0301 (1C10), 1.0503 (1C45), 1.1121 (XC10), 1.1191 (2C45), 1.0718 (S250PB), 1.0736 (S300PB)	Acero no aleado 600 - 850 N/mm² 1.0050 (Fe490-2), 1.0070 (Fe690-2), 1.0301 (F.1151), 1.0503 (F.114), 1.1121 (F.1510-C10K), 1.1191 (C45K), 1.0718 (F.2112-11SMnPb28), 1.0736 (F.2113-11SMn37)	Unlegierter und legierter Stahl 600 - 850 N/mm² 1.0050 (St50-2), 1.0070 (St70-2), 1.0301 (C10), 1.0503 (C45), 1.1121 (Ck10), 1.1191 (C45E), 1.0718 (11SMnPb30), 1.0736 (11SMn37)
P 13 S1000 N/mm ²	P 13 S1000 N/mm ²	Gelegeerd staal 850 - 1000 N/mm² 1.0727 (46S20), 1.0728 (60S20), 1.0757 (46SPb20), 1.2080 (X210Cr12), 1.2083 (X42Cr13), 1.2767 (X45NiCrMo4), 1.5131 (50MnSi4), 1.7003 (38Cr2), 1.7030 (28Cr4), 1.7043 (38Cr4)	Aciers alliés 850 - 1000 N/mm² 1.0727 (45MF4), 1.0728 (60S20), 1.0757 (46SPb20), 1.2080 (Z200C12), 1.2083 (Z40C14), 1.2767 (Y35NCD16), 1.5131 (50MnSi4), 1.7003 (38Cr2), 1.7030 (28Cr4), 1.7043 (38Cr4)	Acero aleado 850 - 1000 N/mm² 1.0727 (46S20), 1.0728 (60S20), 1.0757 (46SPb20), 1.2080 (F.5212-X210Cr12), 1.2083 (X42Cr13), 1.2767 (X45NiCrMo4), 1.5131 (50MnSi4), 1.7003 (38Cr2), 1.7030 (28Cr4), 1.7043 (38Cr4)	Legierter Stahl 850 - 1000 N/mm² 1.0727 (46S20), 1.0728 (60S20), 1.0757 (46SPb20), 1.2080 (X210Cr12), 1.2083 (X42Cr13), 1.2767 (X45NiCrMo4), 1.5131 (50MnSi4), 1.7003 (38Cr2), 1.7030 (28Cr4), 1.7043 (38Cr4)
P 14 S1400 N/mm ²	P 14 S1400 N/mm ²	Gelegeerd staal 1000 - 1400 N/mm² 1.5710 (36NiCr6), 1.7035 (41Cr40), 1.7225 (42CrMo4), 1.8519 (31CrMoV9), 1.8550 (34CrAlNi7), 1.5752 (15NiCr13), 1.7131 (16MnCr5), 1.7264 (20CrMo5)	Aciers alliés 1000 - 1400 N/mm² 1.5710 (36NiCr6), 1.7035 (41Cr40), 1.7225 (42CrMo4), 1.8519 (31CrMoV9), 1.8550 (34CrAlNi7), 1.5752 (15NiCr13), 1.7131 (16MnCr5), 1.7264 (20CrMo5)	Acero aleado 1000 - 1400 N/mm² 1.5710 (36NiCr6), 1.7035 (41Cr40), 1.7225 (42CrMo4), 1.8519 (31CrMoV9), 1.8550 (34CrAlNi7), 1.5752 (15NiCr13), 1.7131 (16MnCr5), 1.7264 (20CrMo5)	Legierter Stahl 1000 - 1400 N/mm² 1.5710 (36NiCr6), 1.7035 (41Cr40), 1.7225 (42CrMo4), 1.8519 (31CrMoV9), 1.8550 (34CrAlNi7), 1.5752 (15NiCr13), 1.7131 (16MnCr5), 1.7264 (20CrMo5)
H 15 HRC	H 15 HRC	Gehard en inzetgehard staal 50 - 60 HRC 1.2344 (X40CrMoV5), 1.2767 (X45NiCrMo4), 1.2379 (X155CrVMo12-1), 1.2080 (X210Cr12), 1.3343 (S6-5-2)	Aciers trempés et Aciers de cémentation alliés 50 - 60 HRC 1.2344 (Z 40 CDV 5), 1.2767 (X45NiCrMo4), 1.2379 (D2), 1.2080 (Z200C12), 1.3343 (Z85WDCV)	Acero templado 50 - 60 HRC 1.2344 (X40CrMoV5), 1.2767 (X45NiCrMo4), 1.2379 (X155CrVMo12-1), 1.2080 (X210Cr12), 1.3343 (S6-5-2)	Gehärteter und einsetzgehärteter Stahl, 50-60 HRC 1.2344 (X40CrMoV5), 1.2767 (X45NiCrMo4), 1.2379 (X155CrVMo12-1), 1.2080 (X210Cr12), 1.3343 (S6-5-2)
M 21 INOX S850N/mm ²	M 21 INOX S850N/mm ²	Roestvaststaal, INOX ≤850 N/mm² 1.4005 (X12CrS13), 1.4104 (X14CrMos17), 1.4105 (X6CrMoS17), 1.4301 (XCrNi18-10)(304), 1.4305 (X8CrNiS18-9)(303)	Aciers inoxydables ≤850 N/mm² 1.4005 (Z11CF13), 1.4104 (Z13CF17), 1.4105 (Z8CF17), 1.4301 (XCrNi18-10)(304), 1.4305 (X8CrNiS18-9)(303)	Acero inoxidable ≤850 N/mm² 1.4006 (F.3401-X10Cr13), 1.4104 (F.3117-X10Cr17), 1.4301 (F.3504-X5CrNi18-10)(304), 1.4305 (F.3508-X10CrNiS18-09)(303)	Rostfreier Stahl, INOX ≤850 N/mm² 1.4005 (X12CrS13), 1.4104 (X14CrMos17), 1.4105 (X6CrMoS17), 1.4301 (XCrNi18-10)(304), 1.4305 (X8CrNiS18-9)(303)
M 22 INOX >850N/mm ²	M 22 INOX >850N/mm ²	Roestvaststaal, INOX >850 N/mm² 1.4438 (X2CrNiMo18-15-4)(317), 1.4404 (X2CrNiMo17-12-2)(316L), 1.4571 (X6CrNiMoTi17-12-2)(316Ti)	Aciers inoxydables >850 N/mm² 1.4438 (X2CrNiMo18-15-4)(317), 1.4404 (X2CrNiMo17-12-2)(316L), 1.4571 (X6CrNiMoTi17-12-2)(316Ti)	Acero inoxidable >850 N/mm² 1.4438 (X2CrNiMo18-15-4)(317), 1.4404 (X2CrNiMo17-12-2)(316L), 1.4571 (F.3535-X6CrNiMoTi17-12-2)(316Ti)	Rostfreier Stahl, INOX >850 N/mm² 1.4438 (X2CrNiMo18-15-4)(317), 1.4404 (X2CrNiMo17-12-2)(316L), 1.4571 (X6CrNiMoTi17-12-2)(316Ti)
K 31 GG	K 31 GG	Grijs gietijzer GG <260 HB30 0.6015 (GG 15), 0.6025 (GG 25), 0.6040 (GG 40)	Fontes <260 HB30 0.6015 (GG 15), 0.6025 (GG 25), 0.6040 (GG 40)	Fundición gris con grafito laminado GG <260 HB30 0.6015 (FG15), 0.6025 (FG25), 0.6040 (FG40)	Grauguss GG <260 HB30 0.6015 (GG 15), 0.6025 (GG 25), 0.6040 (GG 40)
K 32 GGG GTS-GTW	K 32 GGG GTS-GTW	Smeedbaar en Nodulair gietijzer <260 HB30 0.8145 (GTS-45), 0.8170 (GTS-70-02), 0.7040 (GGG 40), 0.7070 (GGG 70)	Fontes à graphites et malléables <260 HB30 0.8145 (GTS-45), 0.8170 (GTS-70-02), 0.7040 (GGG 40), 0.7070 (GGG 70)	Fundición gris con grafito esférico <260 HB30 0.8145 (GTS-45), 0.8170 (GTS-70-02), 0.7040 (GGG 40), 0.7070 (GGG 70)	Formbar und dehnbares Gusseisen <260 HB30 0.8145 (GTS-45), 0.8170 (GTS-70-02), 0.7040 (GGG 40), 0.7070 (GGG 70)
N 41 Alu	N 41 Alu	Aluminium en Aluminiumlegeringen 3.0255 (Al99.5), 3.2315 (AlMgSi1), 3.3515 (AlMg1)	Aluminium et Alliages d'Aluminium 3.0255 (A59050C), 3.2315 (AlMgSi1), 3.3515 (AlMg1)	Aluminio y aleaciones de Aluminio 3.0255 (Al99.5), 3.2315 (AlMgSi1), 3.3515 (AlMg1)	Aluminium und Aluminiumlegierungen 3.0255 (Al99.5), 3.2315 (AlMgSi1), 3.3515 (AlMg1)
N 42 Alu Si>10%	N 42 Alu Si>10%	Gietaluminium Si 10 - 24% 3.2131 (G-AlSi5Cu1), 3.2153 (G-AlSi7Cu3), (3.2573 G-AlSi9), 3.2581 (G-AlSi12), 3.2583 (G-AlSi12Cu)	Alliages d'Aluminium Si 10 - 24% 3.2131 (G-AlSi5Cu1), 3.2153 (G-AlSi7Cu3), (3.2573 G-AlSi9), 3.2581 (G-AlSi12), 3.2583 (G-AlSi12Cu)	Fundición de Aluminio aleada Si 10 - 24% 3.2131 (G-AlSi5Cu1), 3.2153 (G-AlSi7Cu3), (3.2573 G-AlSi9), 3.2581 (L-2520,21), 3.2583 (L2530)	Druckguss Si 10 - 24% 3.2131 (G-AlSi5Cu1), 3.2153 (G-AlSi7Cu3), (3.2573 G-AlSi9), 3.2581 (G-AlSi12), 3.2583 (G-AlSi12Cu)
N 43 Mg	N 43 Mg	Magnesiumlegeringen 3.5200 (MgMn2), 3.5812 (G-MgAl8Zn1), 3.5612 (G-MgAl6Zn1)	Alliages de Magnésium 3.5200 (MgMn2), 3.5812 (AZ81hp), 3.5612 (AZ61)	Aleaciones de Magnesio 3.5200 (MgMn2), 3.5812 (AZ81hp), 3.5612 (AZ61)	Magnesiumlegierungen 3.5200 (MgMn2), 3.5812 (G-MgAl8Zn1), 3.5612 (G-MgAl6Zn1)
N 51 Cu	N 51 Cu	Koper en Koperlegeringen 2.0070 (SE-Cu), 2.1020 (CuSn6), 2.1096 (G-CuSn5ZnPB), 2.0380 (CuZn39Pb2), 2.0401 (CuZn39Pb3), 2.0250 (CuZn20), 2.0280 (CuZn33), 2.0332 (CuZn37Pb0,5)	Cuivres et Alliages de cuivres 2.0070 (SE-Cu), 2.1020 (CuSn6), 2.1096 (G-CuSn5ZnPB), 2.0380 (CuZn40), 2.0401 (CuZn39Pb3), 2.0250 (CuZn20), 2.0280 (CuZn33), 2.0332 (CuZn37Pb0,5)	Cobre y aleaciones de cobre 2.0070 (SE-Cu), 2.1020 (CuSn6), 2.1096 (G-CuSn5ZnPB), 2.0380 (CuZn39Pb2), 2.0401 (CuZn39Pb3), 2.0250 (CuZn20), 2.0280 (CuZn33), 2.0332 (CuZn37Pb0,5)	Kupfer und Kupferlegeringen 2.0070 (SE-Cu), 2.1020 (CuSn6), 2.1096 (G-CuSn5ZnPB), 2.0380 (CuZn39Pb2), 2.0401 (CuZn39Pb3), 2.0250 (CuZn20), 2.0280 (CuZn33), 2.0332 (CuZn37Pb0,5)
N 52 CuAlFe	N 52 CuAlFe	Koper- en Aluminiumlegering 2.0916 (CuAl5), 2.0960 (CuAl9Mn), 2.1050 (CuSn10), 2.0980 (CuAl11Ni), 2.1247 (CuBe2) AMPCO® 8, AMPCO® 8 15, AMPCO® 18	Cuivre et Alliages d'Aluminium 2.0916 (CuAl5), 2.0960 (CuAl9Mn), 2.1050 (CuSn10), 2.0980 (CuAl11Ni), 2.1247 (CuBe1.9) AMPCO® 8, AMPCO® 8 15, AMPCO® 18	Cobre y aleaciones de Aluminio 2.0916 (CuAl5), 2.0960 (CuAl9Mn), 2.1050 (CuSn10), 2.0980 (CuAl11Ni), 2.1247 (CuBe2) AMPCO® 8, AMPCO® 8 15, AMPCO® 18	Kupfer- und Aluminiumlegierungen 2.0916 (CuAl5), 2.0960 (CuAl9Mn), 2.1050 (CuSn10), 2.0980 (CuAl11Ni), 2.1247 (Cu-Be2) AMPCO® 8, AMPCO® 8 15, AMPCO® 18
N 61 PVC	N 61 PVC	Duroplastic en Thermoplastic PMMA, PVC, PE, PP, PTFE	Duroplastiques et Thermoplastiques PMMA, PVC, PE, PP, PTFE	Duroplásticos en Termoplásticos PMMA, PVC, PE, PP, PTFE	Duroplaste und Thermoplaste PMMA, PVC, PE, PP, PTFE
N 62 GFK/CFK	N 62 GFK/CFK	Versterkte kunststoffen GFK, CFK	Plastiques réenforcés GFK, CFK	Plásticos reforzados GFK, CFK	Verstärkte Kunststoffe GFK, CFK
S 71 Ni/Co	S 71 Ni/Co	Nikkel- en Cobaltlegeringen Hastelloy, Inconel, Nimonic, Jetalloy	Alliages de Nickel et de Cobalt Hastelloy, Inconel, Nimonic, Jetalloy	Aleaciones de Niquel y Cobalto Hastelloy, Inconel, Nimonic, Jetalloy	Nickel und Kobaltlegeringen Hastelloy, Inconel, Nimonic, Jetalloy
S 72 Ti	S 72 Ti	Titaniumlegeringen 3.7024 (Ti99.5), 3.7114 (TiAl5Sn2.5), 3.7124 (TiCu2), 3.7154 (TiAl6Zr5), 3.7165 (TiAl6V4), 3.7184 (TiAl4Mo4Sn2.5)	Alliages de Titane 3.7024 (T35), 3.7114 (TiAl5Sn2.5), 3.7124 (T-U2), 3.7154 (TiAl6Zr5), 3.7165 (TiAl6V4), 3.7184 (TiAl4Mo4Sn2.5)	Titanio aleado 3.7024 (Ti99.5), 3.7114 (TiAl5Sn2.5), 3.7124 (TiCu2), 3.7154 (TiAl6Zr5), 3.7165 (TiAl6V4), 3.7184 (TiAl4Mo4Sn2.5)	Titanlegierungen 3.7024 (Ti99.5), 3.7114 (TiAl5Sn2.5), 3.7124 (TiCu2), 3.7154 (TiAl6Zr5), 3.7165 (TiAl6V4), 3.7184 (TiAl4Mo4Sn2.5)